

Managementfunktionen

Basis-Funktionen

	Store und Forward Switching Mode	IEEE 802.3
	Manual und Dynamic IP Address Assignment	
Port-Settings	Auto-Negotiation on / off	
	Port Speed 10 Mbit/s / 100 Mbit/s / 1000 Mbit/s	
	Halb- / Vollduplex	
	Port disable / enable	
	Link Up/Down Trap disable / enable	
	Flow Control disable / enable	
Network Discovery	Link Layer Discovery Protocol (LLDP)	802.1AB, 2005
Protocols	IPv4	RFC 791, 903, 951, 1293, 1519
	TCP	RFC 793, 896
	UDP	RFC 768
	Ethernet ARP	RFC 826
	ICMP	RFC 2521, 1191, 1788, 792
File Transfer	Firmware-Import und -Export via TFTP	
	Configuration-Import und -Export via TFTP	
Time Settings	Manual time setting	
	Simple Network Time Protocol (SNTP)	RFC 1305, RFC 4330
User Management	Admin, Guest und Service Level	
Service	Service Mode via Port 1	
QoS		
	Quality of Service (QoS)	IEEE 802.1p
VLAN		
	Port protocol basierte VLANs	IEEE 802.1Q Rev D5.0, 2005
Redundanz		
	Spanning Tree (STP)	IEEE 802.1D (2004)
	Rapid Spanning Tree (RSTP)	IEEE 802.1D (2004)
Sicherheit		
	Port-Based Network Access Control Port Based Authentication with EAP	802.1x (2004)
	RADIUS Client	RFC 2138
	IP authorized manager	
Link Aggregation		
	Link Aggregation (LACP)	ISO/IEC 8802-3:2005 (E), IEEE 802.3-2005 Edition Clause 43 (IEEE 802.3ad)
Multicast		
	IGMP Snooping (v1, v2, v3) mit Support für Querier	RFC 1112, 2236, 3376
DHCP		
	DHCP Client	RFC 2131
	DHCP relay agent	RFC 2131
	DHCP Option 82	RFC 3046
Alarm		
	Alarmer via E-Mail (SMTP) und SNMP Traps	
	Alarmkontakt für Unterspannung oder Linkänderung	

mCon 3000
mCon 4000
mCon 9000
mCon 7000
A-3
3

Managementfunktionen

Diagnose

	Port Diagnose	
	Port Mirroring	
	Switch History	
	MAC Address Table	
	RMON (1,2,3 & 9 groups)	RFC 2819

Management

	Passwort-geschütztes Web-Management Interface	
	SNMP (v1, v2c, v3) agent & MIB support	RFC 1155, 1157, 1212, 1213, 1215, 2089, 2578, 3411, 3412, 3413, 3414, 3415, 3416, 3417, 3584

MIB Support

	Enterprise (HARTING MIB)	
	MIB II	
	MIB II für SNMPv1, SNMPv2, SNMPv3	
	Interface group MIB	
	Bridge MIB	
	MIB für Ethernet-gemäße Interfaces (benötigt Unterstützung durch die Hardware)	
	VLAN MIB	
	Spanning Tree Protocol MIB	
	Rapid STP MIB	
	Port-based Network Authentication Control MIB	
	Definition der Management-Objecte für LLDP	
	802.1/LLDP Erweiterung MIB	
	802.3/LLDP Erweiterung MIB	
	Radius Client MIB	
	IPv4 MIB	
	IGMP MIB	
	DHCP	

Die beschriebenen Management-Funktionen werden von allen Ethernet Switchen mit der Bezeichnung mCon xxxx-..V unterstützt.

mCon 3000

mCon 4000
mCon 9000

mCon 7000